



High Brightness Short-Throw Projector

FEATURE

- Bright 3,600 ANSI lumens with a high 15,000:1 contrast ratio
- WXGA resolution with a maximum resolution up to WUXGA
- Delivers a 88" diagonal image from less than 1 meter installation distance from the surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Assortment of connectivity options including HDMI 1.4b, VGA, S-Video, Composite Video, Audio-In/Out
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-ray support for dazzling and realistic life-like images
- 6 Segments (RYGCWB) colorwheel for accurate and detailed images
- Sealed optical engine to keep dust out and improve performance
- Integrated 10W audio speakers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad



The DW882ST is designed to cater for the education needs. The DW881ST delivers a 88" diagonal image from less than 1 meter installation distance from the surface. With a brightness of 3,600 ANSI Lumens and contrast ratio of 15,000:1 it delivers a perfect image display. The projector is designed for use in any classroom, small office or at home. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.

DW882ST

EDUCATION



SPECIFICATIONS



| | |
|-----------------------------------|--|
| Display Type | Single 0.65" DLP Technology by TI |
| Brightness | 3,600 ANSI Lumens |
| Native Resolution | WXGA (1280x800) |
| Maximum Resolution | WUXGA (1920x1200)@60Hz |
| Contrast Ratio | 15,000:1 |
| Lamp Life and Type | 3500h/5000h/7000h, UHP Osram 240W/190W (Normal/Eco/Dyn. Eco) |
| Throw Ratio | 0.52 |
| Image Size (Diagonal) | 68" ~ 200" |
| Projection Distance | 0.77 ~ 2.24 |
| Projection Lens | F2.8, f=7.51mm |
| Zoom Ratio | Fixed |
| Aspect Ratio | 16:10 Native |
| Offset (full image height) | 112% (full image height) |
| Keystone Correction | +/-40 Degree; +/- 40 Steps |
| Horizontal Frequency | 15, 31 - 91Hz |
| Vertical Scan Rate | 24 - 30Hz, 47 - 120Hz |
| Lens Shift Range | n/a |
| 3D Compatibility | Yes (DLP® Link™, HDMI 1.4b (Blu-Ray)) |
| Audio | 10W (Mono) |
| Video Compatibility | SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L) |
| I/O Connection Ports | HDMI v1.4b, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack)(x3), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger |
| Security Solutions | Kensington® Security Slot, Security Bar, Keypad Lock |
| Dimensions (WxDxH) | 314 x 216 x 126 mm |
| Weight | 3.2kg |
| Noise Level | 36dB/32dB (Normal/Eco. Mode) |
| Power | Supply: AC 100-240V, 50/60Hz Consumption: 310W (Normal Mode), <0.5W (Standby Mode) |
| Standard Warranty | 3 years projector / 1 year on lamp or 1000 hours whichever comes first |
| Education Warranty | 5 years projector / 3 years on lamp or 2000 hours whichever comes first |
| Standard Accessories | AC Power Cord, VGA Cable, Remote Control, Lens Cap, Documentation Kit |
| Optional Accessories | Replacement Lamp: 5811119560-SVV |
| UPC | 814964 339843 |

© Copyright 2014 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands

tel: +31 20 655 0960 | fax: +31 20 655 0999 | email: info@vivitek.eu