



MHL ready portable projector with Built-in Audio

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- Short throw lens to make 100 inch screen at only 1.3m away
- 3,000 ANSI lumens of brightness and 15,000:1 contrast ratio for clear, crisp and bright presentations
- XGA (1024 x 728) native resolution and support up to maximum WUXGA (1920x1200) resolution
- Compact and lightweight at only 2.3kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- HDMI input for high definition content with the same high quality
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Audio ready with built-in 2 watt audio speaker, audio-in and audio out ports



100 inch big screen at only 1.3 meters away

The DX563ST projector delivers a 100" diagonal image at only 1.3 meters short projection distance from the screen. With a brightness of 3,000 ANSI Lumens and contrast ratio of 15,000:1 it delivers a perfect image display. Featuring a MHL port, DX563ST is compatible for streaming of video and audio content from a compatible mobile device. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.



DX563ST SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3000
	Native Resolution	XGA (1024 x 768)
	Max. Supported Resolution	WUXGA (1600 x 1200) @60Hz
	Native Aspect Ratio	4:3
	Contrast Ratio	15,000:1
	Keystone Correction	Vertical +/-40°
	Optical	Throw Ratio
Zoom Ratio		1x
Image Size (Diagonal)		50" - 126"
Projection Distance		660 - 1690 mm
Projection Lens		F = 2.87, f = 7.28 mm
Offset (Based on Full Image Height)		114%
Features		3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock, Wall Color Correction
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI v 1.4 (HDMI/MHLx1), Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), 12v Trigger, RS-232, USB miniB (Service)
General	Dimensions (W x D x H)	274.6 x 212 x 100 mm
	Weight	2,3
	Power	Supply: AC 100-240V, 50/60Hz, Consumption: 200W (Eco. Mode), 240W (Normal Mode), <0.5W (Standby)
	Lamp Life and Type	5,000/6,000/10,000 Hours (Normal/Eco./Dynamic Eco. Mode), 190W/160W
	Speakers	2W
	Noise Level	35dB/31dB (Normal/Eco; Mode)
	Standard Accessories	VGA Cable, User Manual (CD), Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811118154-SVV), Remote Control P/N (5041849100), Carrying Case P/N (3523504000)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1000 hours whichever comes first
	UPC Code	813097 021502